



Features

Heavy duty high speeds and high quality sander for metalworking applications.

1 Gearless alloy steel motor design

Provides long service life and reduce maintenance costs.



2 Safety-lock trigger

Prevent accidental start the tool.

3 360° swivel air exhaust.



4 Ergonomic handle grip

Provide excellent controllability during work.

5 7 degree handle offset design

Enhances tool ergonomics for better comfort of use.

ST-AS32N3R 0.5HP

3" Air Angle Sander
20,000 rpm



ST-AS31N2R 0.4HP

2" Air Angle Sander
30,000 rpm



Specification:

★ Recommend Air Pressure 6.2 bar (90psi)

Model No.	Horsepower		Pad Size		Free Speed (r.p.m)	Spindle Size	Overall Length		Air Inlet (PT)	Air Hose (I.D.)	Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kgs)
	hp	w	in	mm			mm	in			l/min	cfm	kgs	lbs	
ST-AS32N3R	0.5	373	3	76	20,000	1/4" -20 UNF	185	7-2/7	1/4"	3/8"	370	13	0.75	1.65	10Pcs/Ctn/10.5/1.2'
ST-AS31N2R	0.4	224	2	51	30,000	1/4" -20 UNF	180	7	1/4"	3/8"	370	13	0.48	1.06	20Pcs/Ctn/14/1.1'

SUMAKE Industrial Co., Ltd.

4F, No.351, Yangguang St., Neihu District, Taipei, Taiwan, Zip:114-91

Tel: 886-2-2659-3500

http: //www.sumake.com

Fax: 886-2-2659-3700

e-mail: sales@sumake.com.tw



Certificate TW04/02301



XPST-GR22-0930