

0.45HP Flex-Head Air Tool Series

SUMAKE
MAKE JOBS BETTER THAN EVER

Tool-free Angle Adjustment . Effortlessly.


Application

Perfectly designed for applications in tight and hard-to-reach spaces.
It is suitable for car body refinishing work, particularly for surface detailing.
Tool-free angle adjustment allows for effortless operation.



Gearless angle head with built-in powerful 0.45HP air motor

Composite body to make better weight balance and improve ergonomics and reduce hand strain



360° Swivel Air Exhaust Design



Safety-Lock Lever


Speed setting with three positions for easy two-finger operation

Tool-free flexible multi-angle adjustment for various work directions and hand-holding needs

ST-AS14N2H 2" Pad

ST-AS14N3H 3" Pad

Air Orbital Sander w/ Hook Pad
17,000 rpm



ST-AS14N2R 2" Pad

ST-AS14N3R 3" Pad

Air Rotary Sander w/ Roloc Disc Pad
17,000 rpm



ST-AP1402H 2" Pad

ST-AP1403H 3" Pad

Air Polisher w/ Hook Pad
2,800 rpm



ST-DG1402L 1/4"

ST-DG1406L 6mm

Air Angle Die Grinder
18,000 rpm



ST-AD1403K 3/8"

Air Angle Drill

ST-AD1403C 3/8"
w/ Keyless Chuck
3,000 rpm

Specification:

★ Recommend Air Pressure 6.2 bar (90psi)

Model No.	Pad Size		Spindle	Free Speed (r.p.m)	Overall Length		Air Inlet (PT)	Air Hose (I.D.)	Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kgs)
	in	mm			mm	in			l/min	cfm	kgs	lbs	
ST-AS14N2(3)H	2 or 3	50 or 75	5/16"-24T	17,000	206 x 50 x 100	8-1/9 x 2 x 4	1/4"	3/8"	283	10	0.75	1.65	10Pcs/Ctn/10/0.8'
ST-AS14N2(3)R	2 or 3	50 or 75	1/4"-20T	17,000	206 x 50 x 96	8-1/9 x 2 x 3-7/9	1/4"	3/8"	283	10	0.66	1.46	10Pcs/Ctn/9/0.8'
ST-AP1402(3)H	2 or 3	50 or 75	5/16"-24T	2,800	206 x 50 x 108	8-1/9 x 2 x 4-1/4	1/4"	3/8"	283	10	0.84	1.85	10Pcs/Ctn/10/0.8'

Model No.	Collet		Free Speed (r.p.m)	Overall Length		Air Inlet (PT)	Air Hose (I.D.)	Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kgs)
	in	mm		mm	in			l/min	cfm	kgs	lbs	
ST-DG1402(6)L	1/4	6	18,000	210 x 50 x 100	8-1/4 x 2 x 4	1/4"	3/8"	283	10	0.75	1.65	10Pcs/Ctn/9/0.8'

Model No.	Drilling Cap		Free Speed (r.p.m)	Overall Length		Air Inlet (PT)	Air Hose (I.D.)	Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kgs)
	mm	in		mm	in			l/min	cfm	kgs	lbs	
ST-AD1403K	10	6	3,000	206 x 50 x 140	8-1/9 x 2 x 5-1/2	1/4"	3/8"	283	10	1.03	2.27	10Pcs/Ctn/12/0.8'
ST-AD1403C	10	6	3,000	206 x 50 x 153	8-1/9 x 2 x 6	1/4"	3/8"	283	10	1.03	2.27	10Pcs/Ctn/12/0.8'

SUMAKE Industrial Co., Ltd.

4F, No.351, Yangguang St., Neihu District, Taipei, Taiwan, Zip:114-91

Tel: 886-2-2659-3500

Fax: 886-2-2659-3700

http: //www.sumake.com

e-mail: sales@sumake.com.tw



Certificate TW04/02301



XPST-GR23-0925(R2)