

Vibration-Reduction Air Hammer

SUMAKE
MAKE JOBS BETTER THAN EVER

Increase Power by 30%. Reduce Vibration by 70%.



Application

Long-barrel type — ideal for heavy-duty jobs such as separating ball joints, cutting large bolts, and driving bushings.
Medium-barrel type — ideal for medium-duty jobs commonly found in body shops, such as cutting sheet metal, separating or cutting frame rails, and removing rivets.

Feature

Extremely powerful handheld tool.

Integrated quick-change retainer

For quick chisel installation.

Damping System

Provide more powerful hammer beating while yielding low vibration.

Active Air Spring

The air spring design makes an air chamber filled with compressed air, creating an air suspension to absorb back and forward movement vibration.

Front exhaust design

Direct air away from the user.

Sensitive trigger

Easier variable blows per minute.

Comfortable housing

Soft grip is co-molded with the composite housing for comfortable and durability.

Four Stages Built-in Air Regulator

Adjustable power for versatile applications.



Medium barrel
ST-AH613R-Q Round:0.41"
ST-AH613H-Q Hex:10mm
ST-AH614H-Q Hex:11mm
 3,500 b.p.m.



Long-barrel
ST-AH615R-Q Round:0.41"
ST-AH615H-Q Hex:10mm
ST-AH616H-Q Hex:11mm
 2,500 b.p.m.

Specification:

★ Recommend Air Pressure 6.2 bar (90psi)

Model No.	Chisel Shank	Bore Diameter (I.D.)		Piston Stroke Length		Blow Per Min. (b.p.m.)	Overall Length		Air Inlet (PT)	Air Hose (I.D.)	Air Consumption		New Weight		Packing Pcs/Ctn/G.W./Cuft (kgs)
		mm	inch	mm	inch		mm	inch			l/min	cfm	kgs	lbs	
ST-AH613R-Q	Round:0.41"	19	3/4	58	2-2/7	3,500	240	9.4	1/4"	3/8"	480	17	2	4.4	6Pcs/Ctn/15.2/0.95'
ST-AH613H-Q	Hex:10mm	19	3/4	58	2-2/7	3,500	240	9.4	1/4"	3/8"	480	17	2	4.4	6Pcs/Ctn/15.2/0.95'
ST-AH614H-Q	Hex:11mm	19	3/4	58	2-2/7	3,500	240	9.4	1/4"	3/8"	480	17	2	4.4	6Pcs/Ctn/15.2/0.95'
ST-AH615R-Q	Round:0.41"	19	3/4	89	3-1/2	2,500	290	11.4	1/4"	3/8"	480	17	2.3	5	6Pcs/Ctn/17.5/1.21'
ST-AH615H-Q	Hex:10mm	19	3/4	89	3-1/2	2,500	290	11.4	1/4"	3/8"	480	17	2.3	5	6Pcs/Ctn/17.5/1.21'
ST-AH616H-Q	Hex:11mm	19	3/4	89	3-1/2	2,500	290	11.4	1/4"	3/8"	480	17	2.3	5	6Pcs/Ctn/17.5/1.21'

SUMAKE Industrial Co., Ltd.

4F, No.351, Yangguang St., Neihu District, Taipei, Taiwan, Zip:114-91
 Tel: 886-2-2659-3500 Fax: 886-2-2659-3700
 http://www.sumake.com e-mail: sales@sumake.com.tw



Certificate TW04/02301



XPST-H25-1002(R1)