



SUMAKE Industrial Co., Ltd.

Sample of configuration

Maintenance Checklist

Company Name :			
MODEL NO. :			
S/N:			
P/I or Order no.:	11		
Problem statement:			
Filled Date:			

	SUMRKE Valve Air compressor Air dryer	Air Tank pipe & air pressure Secondary air pressure	air pipe	tion.
Diag	nactics		Filled by ma	nufacturer
Diagi	nostics		ОК	NG
1	The length of Main air pipe for Production line	☐ Over 60m ☐ 30m ☐ 15m ☐ 5m ☐ Othersm		
2	The diameter of Main air pipe for Production line	☐ 25mm ☐ 20mm ☐ 15mm ☐ 10mm ☐ Othersmm		
3	The air pressure of Secondary air pipe for Production line	☐ 6Kg/cm2 ☐ 5Kg/cm2 ☐ 4Kg/cm2 ☐ OthersKg/cm2		
4	The length of Secondary air pipe for Production line	☐ Over 10m ☐ 5m ☐ 3m ☐ 2m ☐ 1m ☐ Othersm		
5	The diameter of Secondary air pipe for Production line	☐ 12mmX8mm ☐ 10mmX6.5mm ☐ 8mmX5mm ☐ 6mmX4mm ☐ Othersmm		
6	The air pressure of Third air pipe for Production line (press trigger)			
7	The length of Third air pipe for Production line	☐ Over 10m ☐ 5m ☐ 3m ☐ 2m ☐ 1m ☐ Othersm		
8	The diameter of Third air pipe for Production line	☐ 12mmX8mm ☐ 10mmX6.5mm ☐ 8mmX5mm ☐ 6mmX4mm ☐ Othersmm		70
9	The air equipment of Production line	☐ Dryer ☐ Pressure Regulator ☐ Oil feed ☐ Water filter		





SUMAKE Industrial Co., Ltd.

Maintenance Checklist

Diag	nostics	Filled by manufacturer		
Diag	iiosucs		OK	NG
10	Torque value (indicate when insufficient torque)	☐ Test by Hydraulic torque test ☐ Test by Digital torque test ☐ Other ft-lb N.m in-lb unders(time)		
11	Application	☐ Production line ☐ Maintenance ☐ Automotive after service		
12	The size of bolt(diameter)	mm		
13	The size of bolt(length)	mm		
14	The material of festening	☐ Steel ☐ Steel(Tapping) ☐ Wood ☐ Plastics ☐ Others		
15	Frequency of operation	hr/day, Screwing count Total operating days days		>0
Mair	tenance points- An Abnorma	al problem		/
1	Check general condition for Bit	□The Bit slide sleeve has broken □The C Ring is fell off from bit slide sleeve □The Ball is felling apart from bit slide sleeve □Others		
2	Check general condition for Looking	□The switch has broken or damage □The Soft cover is fall off from tool □The Torque Ring was bumped □Others		
3	Visual check of Running for tools	□The Clutch has loosened from anvil □The Valve Plate or Balls did not in anvil □The O Ring is felling apart from end housing □Others		
4	Check of the brake time for the screw M5 of anvil	□ The End Housing has lossened from center housing □ The Clutch is abrasion from anvil □ The screw M3 x20 for dust □ Others		
5	Check condition of torque	□Three pins of torque ring was fell off from clutch housing □The Clutch is abrasion from anvil □The Torque Spring has broken □Others		
6	Check Motor running in abnormal	□The Motor is rusty □The Blade has broken □The Gear has broken □The Bearing has broken or a bit rusty □Others		A
7	Insufficient power for torque and speed	□Check of the Silencer for dust. □The End Housing has lossened from center housing. □The Clutch is abrasion from anvil. □The Torque Spring is fatigued. □Others	V	
Rema	rks:		V	