


All of SUMAKE air nailer & stapler programs are CE standard implied, take easy in your mind.
We have four kinds of actuation as the below information & attached video:

| | | | 1 st shot | 2 nd shot | REMARK |
|---|--|--|--|---|--|
| 1 | SAFETY DEVICE | Single fire Please click here for attached video | Touch the work-piece first and press the lever | Repeating the action as 1 st shot. | Based on CE standard, the length is more than 25mm then safety device must imply. ★F18/30& P0.6/30 are not implied. It is because these two models are for Asian market. However if needed, the safety device can employed which the safety device would similar to F18/32. |
| 2 | | Bumper fire Please click here for attached video | Press the lever first and touch the work-piece | No need to release the lever, just keep continuing touch the work-piece. | |
| 3 | | Sequential fire Please click here for attached video | Press the lever first and touch the work-piece. | Un-touch work-piece& release the lever are needed. Then repeating actions in 1st shot. *** Mainly used in construction purpose: R-65 / R-100 | |
| 4 | SIMPLE SAFETY LEVER Please click here for attached video | | Rotate the below indicated safety switch and press the lever.  | Simply press the lever. ★ CAUTION: Nail can keep firing even NOT touch the work-piece. | Base on CE standard, the length shorter than 25mm only need safety lever. |